

FEDERAL ITEM IDENTIFICATION GUIDE
HEADSET-CHEST SET, ELECTRICAL
ITEM NAME CODE
00710



Commander
Defense Logistics Information Service
ATTN: DLIS-K
74 Washington Avenue North, Suite 7
Battle Creek, Michigan 49037-3084
(COMM) (269) 961-5779
(DSN) 661-5779

This Federal Item Identification Guide for Supply Cataloging is issued under the authority of Department of Defense Instruction 5025.7.

The use of this publication is mandatory for US. Federal Activities participating in Federal Catalog System Operations.

BY ORDER OF THE DIRECTOR

/s/

Commander

Defense Logistics Information Service

Table of Contents

SECTION I	4
Reply Tables	13
Reference Drawing Groups.....	17
FIIG Change List	18

SECTION I

MRC	Mode Code	Requirements
NAME	D	ITEM NAME

Definition: A NOUN, WITH OR WITHOUT MODIFIERS, BY WHICH AN ITEM OF SUPPLY IS KNOWN.

Reply Instructions: Enter the Item Name Code applicable to this FIIG. (e.g., NAMED00710*)

AHES A EARPHONE QUANTITY

Definition: THE NUBER OF EARPHONES PROVIDED ON THE ITEM.

Reply Instructions: Enter the quantity. (e.g., AHESA2*)

BKSQ J EARPHONE IMPEDANCE RATING

Definition: THE TOTAL OPPOSITION (RESISTIVE AND REACTIVE) WHICH THE EARPHONE OFFERS TO THE FLOW OF ALTERNATING CURRENT.

Reply Instructions: Enter the applicable Reply Codes from Tables 1 and 2 below, followed by the numeric value. (e.g., BKSQJQRA600.0*; BKSQJQRB12.5\$\$JQRC17.5*)

<u>REPLY CODE</u>	<u>REPLY (AE75)</u>
KR	KILOHMS
QR	OHMS

<u>REPLY CODE</u>	<u>REPLY (AC20)</u>
A	NOMINAL
B	MINIMUM
C	MAXIMUM

BKSR J EARPHONE DC IMPEDANCE RATING

Definition: THE OPPOSITION TO THE FLOW OF DIRECT CURRENT OFFERED BY AN EARPHONE.

Reply Instructions: Enter the applicable Reply Codes from Tables 1 and 2 below, followed by the numeric value. (e.g., BKSRJQRA350.0*; BKSRJQRB300.0\$\$JQRC400.0*; BKSRJQRA350.0\$JQRA360.0*)

FIIG A545Q
INC 00710
SECTION I

REPLY CODE
KR
QR

REPLY (AE75)
KILOHMS
OHMS

REPLY CODE
A
B
C

REPLY (AC20)
NOMINAL
MINIMUM
MAXIMUM

BKSW D MICROPHONE ELEMENT TYPE

Definition: INDICATES THE TYPE OF MICROPHONE ELEMENT OR CARTRIDGE AS DETERMINED BY ITS CONSTRUCTION AND METHOD OF OPERATION.

Reply Instructions: Enter the applicable Reply Code from the table below. (e.g., BKSWDAGS; BKSWDNL\$\$AGT*)*

REPLY CODE
AGS
AGT
AGU
AGV
AGW
AGX

REPLY (AC58)
CARBON
CRYSTAL
DIAPHRAGM
DYNAMIC
MAGNETIC
SOUND VIBRATION

AFYY J IMPEDANCE RATING*

Definition: THE TOTAL OPPOSITION (RESISTIVE AND REACTIVE) TO THE FLOW OF ALTERNATING CURRENT.

Reply Instructions: Enter the applicable Reply Codes from Tables 1 and 2 below, followed by the numeric value. (e.g., AFYYJQRA600.0; AFYYJQRB550.0\$\$JQRC650.0*)*

REPLY CODE
KR
QR

REPLY (AE75)
KILOHMS
OHMS

REPLY CODE
A

REPLY (AC20)
NOMINAL

FIIG A545Q
INC 00710
SECTION I

B	MINIMUM
C	MAXIMUM

AFYV* J DC RESISTANCE RATING IN OHMS

Definition: THE OPPOSITION TO THE FLOW OF DIRECT CURRENT OFFERED BY AN ITEM, EXPRESSED IN OHMS.

Reply Instructions: Enter the applicable Reply Code from the table below, followed by the numeric value. (e.g., AFYVJA350.0, AFYNJB40.0\$\$JC100.0*)*

<u>REPLY CODE</u>	<u>REPLY (AC20)</u>
A	NOMINAL
B	MINIMUM
C	MAXIMUM

APAM* J OPERATING CURRENT RATING

Definition: THE OPERATING CURRENT FOR WHICH THE ITEM IS RATED.

Reply Instructions: Enter the applicable Reply Codes from Tables 1 and 2 below, followed by the numeric value. (e.g., APAMJAA1.2; APAMJAB3.0\$\$JAC5.0*)*

<u>REPLY CODE</u>	<u>REPLY (AC30)</u>
A	AMPERES
L	MILLIAMPERES

<u>REPLY CODE</u>	<u>REPLY (AC20)</u>
A	NOMINAL
B	MINIMUM
C	MAXIMUM

ACZB* J FREQUENCY RATING

Definition: THE NUMBER OF COMPLETE CYCLIC CHANGES, PER UNIT OF TIME, FOR WHICH THE ITEM IS RATED.

Reply Instructions: Enter the applicable Reply Codes from Tables 1 and 2 below, followed by the numeric value. (e.g., ACZBJEA60.0; ACZBJEB50.0\$\$JEC60.0*; ACZBJEA50.0\$JEA60.0)*

FIIG A545Q
INC 00710
SECTION I

REPLY CODE

E
K

REPLY (AC32)

HERTZ
KILOHERTZ

REPLY CODE

A
B
C

REPLY (AC20)

NOMINAL
MINIMUM
MAXIMUM

*BKSX * G OUTPUT LEVEL RATING*

Definition: AN INDICATION OF THE RATED ELECTRICAL OUYPUT OF THE ITEM.

Reply Instructions: Enter the in clear text. (e.g., BKSXG12 DB BELOW 6 MW OUTPUT LEVEL)*

*AMSA * G CONTROLLING AGENCY*

Definition: THE NAME OF THE GOVERNMENT AGENCY OR COMMERCIAL ORGANIZATION CONTROLLING THE ITEM.

Reply Instructions: Enter the reply in clear text. (e.g., AMSAGDAVIS CORP.)*

*AMSB * J IDENTIFYING NUMBER*

Definition: AN IDENTIFYING NUMBER ASSIGNED BY THE GOVERNMENT AGENCY OR COMMERCIAL ORGANIZATION CONTROLLING THE ITEM.

Reply Instructions: Enter the applicable Reply Code from the table below, followed by the identifying number. (e.g., AMSBJAD101760; AMSBJAD101760\$\$JAF208A*; AMSBJAC89596B\$JAC89596C*)*

REPLY CODE

AB
AC
AD
EA
AF

REPLY (AG99)

DRAWING NO.
MODEL NO.
PART NO.
SERIAL MO.
TYPE NO.

BKSZ D MICROPHONE MOUNTING FACILITY*

Definition: THE MEANS PROVIDED TO MOUNT OR OTHERWISE ACCOMMODATE A MICROPHONE.

Reply Instructions: Enter the applicable Reply Code from Appendix A, Table 1. (e.g., BKSZDAZG; BKSZDBBK\$\$DANF*; BKSZDBBF\$DAZF*)*

FEAT * G SPECIAL FEATURES

Definition: THOSE UNUSUAL OR UNIQUE CHARACTERISTICS OR QUALITIES OF AN ITEM NOT COVERED IN THE OTHER REQUIREMENTS AND WHICH ARE DETERMINED TO BE ESSENTIAL FOR IDENTIFICATION.

Reply Instructions: Enter the reply in clear text. (e.g., FEATGQUALITY CONTROLLED*)

ZZZK * J SPECIFICATION/STANDARD DATA

Definition: THE DOCUMENT DESIGNATOR OF THE SPECIFICATION OR STANDARD WHICH ESTABLISHED THE ITEM OF SUPPLY.

Reply Instructions: Enter the applicable Reply Code from the table below, followed by the Commercial and Government Entity (CAGE) Code of the entity controlling the document, a dash, and the document designator. The agency that controls the limited coordination document must be preceded and followed by a slash following the designator. The word canceled or superseded must be preceded and followed by a slash for the designator. Professional and industrial association specifications/standards are differentiated from a manufacturer's specification in that the data has been coordinated and published by the professional and industrial association. Include amendments and revisions where applicable.

(e.g., ZZZKJT81337-30642B*;

ZZZKJS81349-MIL-D-180 REV1/CANCELED/*;

ZZZKJP80205-NAS1103*;

ZZZKJS81349-MIL-C-1140C/CE/*;

ZZZKJT81337-30642B\$\$JP80205-NAS1103*)

<u>REPLY CODE</u>	<u>REPLY (AN62)</u>
S	GOVERNMENT SPECIFICATION
T	GOVERNMENT STANDARD
D	MANUFACTURERS SOURCE CONTROL
R	MANUFACTURERS SPECIFICATION
N	MANUFACTURERS SPECIFICATION CONTROL
M	MANUFACTURERS STANDARD
A	PROFESSIONAL/INDUSTRIAL ASSOCIATION SPECIFICATION
P	PROFESSIONAL/INDUSTRIAL ASSOCIATION STANDARD

FIIG A545Q
INC 00710
SECTION I

ZZZT * J NONDEFINITIVE SPEC/STD DATA

NOTE: If the specification/standard cited in reply to MRC ZZZK is nondefinitive, reply to MRC ZZZT. This reply is the data which is not recorded in Segment C.

Definition: THE NUMBER, LETTER, OR SYMBOL THAT INDICATES THE TYPE, STYLE, GRADE, CLASS, AND THE LIKE, OF AN ITEM IN A NONIDENTIFYING SPECIFICATION OR STANDARD.

Reply Instructions: Enter the applicable Reply Code from [Appendix A](#), Table 2, followed by the appropriate number, letter, or symbol. (e.g., ZZZTJTY1; ZZZTJTY1\$\$JSTA*; ZZZTJTY1\$JSTA*)*

ZZZY * G REFERENCE NUMBER DIFFERENTIATING CHARACTERISTICS

Definition: A FEATURE OF THE ITEM OF SUPPLY WHICH MUST BE SPECIFICALLY RECORDED WHEN THE REFERENCE NUMBER COVERS A RANGE OF ITEMS.

Reply Instructions: Enter the reply in clear text. (e.g., ZZZYGCOLOR CODED LEADS*; ZZZYGAS DIFFERENTIATED BY MATERIAL*)

CRTL * A CRITICALITY CODE JUSTIFICATION

Definition: THE MASTER REQUIREMENT CODES OF THOSE REQUIREMENTS WHICH ARE TECHNICALLY CRITICAL BY REASON OF TOLERANCE, FIT, PERFORMANCE, OR OTHER CHARACTERISTICS WHICH AFFECT IDENTIFICATION OF THE ITEM.

Reply Instructions: Enter the Master Requirement Code for the requirement, the reply to which renders the item as being critical. (e.g., CRTLAAKJA*; CRTLAAKJA\$\$ACSGS*)

Reply to this requirement only if the header record for the item identification for the item being identified has been coded as critical.

PRPY * A PROPRIETARY CHARACTERISTICS

NOTE: If Document Availability Code B, D, F, or H, reply to MRC PRPY.

Definition: IDENTIFICATION OF THOSE CHARACTERISTICS INCLUDED IN THE DESCRIPTION FOR WHICH A NON-GOVERNMENT ACTIVITY HAS IDENTIFIED ALL OR SELECTED CHARACTERISTICS OF THE ITEM AS BEING PROPRIETARY AND THEREFORE RESTRICTED FROM RELEASE OUTSIDE THE GOVERNMENT WITHOUT PRIOR PERMISSION OF THE ORIGINATOR OF THE DATA.

FIIG A545Q
INC 00710
SECTION I

Reply Instructions: Enter the MRC codes of the individual characteristics of the description which are marked proprietary on the technical data, using AND coding (\$\$) for multiple characteristics. If all the MRCs are proprietary, enter the reply PACS. If none of the MRCs is proprietary, enter the reply NPAC. (e.g., PRPYAPACS*; PRPYANPAC*; PRPYAAKJA\$\$ACSGS*)

TEST * J TEST DATA DOCUMENT

Definition: THE SPECIFICATION, STANDARD, DRAWING, OR SIMILAR INSTRUMENT THAT SPECIFIES ENVIRONMENTAL AND PERFORMANCE REQUIREMENTS OR TEST CONDITIONS UNDER WHICH AN ITEM IS TESTED AND ESTABLISHES ACCEPTABLE LIMITS WITHIN WHICH THE ITEM MUST CONFORM IDENTIFIED BY AN ALPHABETIC AND/OR NUMERIC REFERENCE NUMBER. INCLUDES THE COMMERCIAL AND GOVERNMENT ENTITY (CAGE) CODE OF THE ENTITY CONTROLLING THE INSTRUMENT.

Reply Instructions: Enter the applicable Reply Code from the table below, followed by the 5-position CAGE code, a dash, and the document identification number. (e.g., TESTJA12345-CWX654321*; TESTJA12345-654321\$\$JB55566N66354*; TESTJA12345-654321\$JB55566-663654*)

<u>REPLY CODE</u>	<u>REPLY (AC28)</u>
A	SPECIFICATION (Includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "nominal", etc.)
B	STANDARD (Includes industry or association standards, individual manufacturer standards, etc.)
C	DRAWING (This is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc; excludes any specification, standard, or other document that may be referenced in a basic governing drawing.)

ELRN * G EXTRA LONG REFERENCE NUMBER

Definition: A REFERENCE NUMBER EXCEEDING 32 POSITIONS.

FIIG A545Q
INC 00710
SECTION I

Reply Instructions: Enter the entire reference number. Do not include the 5-position Commercial and Government Entity (CAGE) Code unless there is more than one extra long reference number on the NSN, (e.g., ELRNGANN112036BIL060557LEN313605UZ62365*).

If there is more than one extra long reference number on the NSN, include the CAGE or NCAGE and separate each reference by using the "&" character, (e.g., 28480 ANN112036BIL060557LEN313605UZ62365 & S1234 NN112036BIL060557LEN313605UZ62365).

In determining quantity of characters in the reference number, count will be made after modification in accordance with Volume 2, Chapter 9, FLIS Procedures Manual, DoD 4100.39-M.

CLQL * G COLLOQUIAL NAME

Definition: A COMMON USAGE NAME BY WHICH AN ITEM IS KNOWN.

Reply Instructions: Enter the reply in clear text. (e.g., CLQLGWOVEN WIRE CLOTH*)

ENAC* D ENVIRONMENTAL ATTRIBUTE CODE

Definition: INDICATES THE TYPE OF PRODUCT THAT MEETS OR EXCEEDS THE GOVERNMENT GUIDELINES FOR ENVIRONMENTALLY PREFERRED CHARACTERISTICS.

Reply Instructions: Enter the applicable Reply Code from the table below. (e.g., ENACDHI)*

REPLY
CODE
HI

REPLY (EN02)

*ENERGY EFFICIENT - FEMP - LOW STANDBY
POWER -*

AGAV * G END ITEM IDENTIFICATION

Definition: THE NATIONAL STOCK NUMBER OR THE IDENTIFICATION INFORMATION OF THE END EQUIPMENT FOR WHICH THE ITEM IS A PART.

Reply Instructions: Enter the applicable reply in clear text.

(e.g., AGAVG3930-00-000-0000*;

AGAVGFORKLIFT TRUCK, SMITH CORPORATION, MODEL 12, TYPE A*)

FIIG A545Q
INC 00710
SECTION I

CXCY * G PART NAME ASSIGNED BY CONTROLLING AGENCY

Definition: THE NAME ASSIGNED TO THE ITEM BY THE GOVERNMENT AGENCY OR COMMERCIAL ORGANIZATION CONTROLLING THE DESIGN OF THE ITEM.

Reply Instructions: Enter the reply in clear text. (e.g., CXCYGLINE PROCESSOR CONTROL BOARD*)

Reply Tables

Table 1 - *ATTACHMENT METHOD*..... 14

Table 2 - NONDEFINITIVE SPEC/STD DATA..... 14

Table 1 - *ATTACHMENT METHOD*
ATTACHMENT METHOD

<u>REPLY CODE</u>	<u>REPLY (AM39)</u>
ABH	CLAMP
AFL	CLIP
APF	PLUG
AJK	SNAP FASTENER
AZF	SNAP SPRING HOLDER
ANF	SPRING CLIP
AZG	THUMB SCREW

Table 2 - NONDEFINITIVE SPEC/STD DATA
NONDEFINITIVE SPEC/STD DATA

<u>REPLY CODE</u>	<u>REPLY (AD08)</u>
AL	ALLOY
AN	ANNEX
AP	APPENDIX
AC	APPLICABILITY CLASS
AR	ARRANGEMENT
AS	ASSEMBLY
AB	ASSORTMENT
BX	BOX
CY	CAPACITY
CA	CASE
CT	CATEGORY
CL	CLASS
CE	CODE
CR	COLOR
CC	COMBINATION CODE
CN	COMPONENT
CP	COMPOSITION
CM	COMPOUND
CD	CONDITION
CS	CONSTRUCTION
DE	DESIGN
DG	DESIGNATOR
DW	DRAWING NUMBER
EG	EDGE
EN	END
FY	FAMILY
FG	FIGURE
FN	FINISH
FM	FORM
FA	FORMULA

<u>REPLY CODE</u>	<u>REPLY (AD08)</u>
GR	GRADE
GP	GROUP
NS	INSERT
TM	ITEM
KD	KIND
KT	KIT
LG	LENGTH
LT	LIMIT
MK	MARK
ML	MATERIAL
MH	MESH
ME	METHOD
MD	MODEL
MT	MOUNTING
NR	NUMBER
PT	PART
PN	PATTERN
PC	PHYSICAL CONDITION
PS	PIECE
PL	PLAN
PR	POINT
QA	QUALITY
RN	RANGE
RT	RATING
RF	REFERENCE NUMBER
SC	SCHEDULE
SB	SECTION
SL	SELECTION
SE	SERIES
SV	SERVICE
SX	SET
SA	SHADE
SH	SHAPE
SG	SHEET
SZ	SIZE
PZ	SPECIES
SQ	SPECIFICATION SHEET
SD	SPEED
ST	STYLE
SS	SUBCLASS
SF	SUBFORM
SP	SUBTYPE
SN	SURFACE CONDITION
SY	SYMBOL
SM	SYSTEM
TB	TABLE
TN	TANNAGE
TP	TEMPER

<u>REPLY CODE</u>	<u>REPLY (AD08)</u>
TX	TEXTURE
TK	THICKNESS
TT	TREATMENT
TR	TRIM
TY	TYPE
YN	UNIT
VA	VARIETY
WT	WEIGHT
WD	WIDTH

Reference Drawing Groups

No table of contents entries found.

FIIG Change List

FIIG Change List, Effective February 5, 2010

New FIIG.